



# **Elastomeric Selectively Permeable Membranes For Chemical and Biological Protective Clothing**

**Quoc Truong**  
Physical Scientist

**U.S. Army Soldier, and Biological  
Chemical Command (SBCCOM)  
Soldier Systems Center (SSC)  
Natick, MA 01760-5019**

**OFFICE SYMBOL: AMSSB-RIP-C(N)  
COM: (508) 233-5484; DSN: 256-5484  
FAX: (508) 233-4994 or 4331  
EMAIL: [quoc.truong@natick.army.mil](mailto:quoc.truong@natick.army.mil)**

Report Documentation Page				Form Approved OMB No. 0704-0188	
Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.					
1. REPORT DATE <b>01 JUL 2003</b>		2. REPORT TYPE <b>N/A</b>		3. DATES COVERED <b>-</b>	
4. TITLE AND SUBTITLE <b>Elastomeric Selectively Permeable MembranesFor Chemical and Biological Protective Clothing</b>				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S)				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) <b>U.S. Army Soldier, and Biological Chemical Command (SBCCOM) Soldier Systems Center (SSC) Natick, MA 01760-5019</b>				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION/AVAILABILITY STATEMENT <b>Approved for public release, distribution unlimited</b>					
13. SUPPLEMENTARY NOTES <b>See also ADM001523., The original document contains color images.</b>					
14. ABSTRACT					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT <b>UU</b>	18. NUMBER OF PAGES <b>12</b>	19a. NAME OF RESPONSIBLE PERSON
a. REPORT <b>unclassified</b>	b. ABSTRACT <b>unclassified</b>	c. THIS PAGE <b>unclassified</b>			

# •ADVANCED LIGHTWEIGHT CB PROTECTION PROGRAM (DTO CB-06a-12-D) WAS SUCCESSFULLY COMPLETED IN FY00, WHERE SPM UNIFORMS WERE PREFERRED OVER CURRENT CHEMICAL PROTECTIVE GARMENTS

## Accomplishments:

Developed and demonstrated SPM garments that are 50% lighter weight than any fielded garment with equivalent or better protection.

Integrated novel closure systems and demonstrated their effectiveness via MIST @ERDEC, @DPG


Conducted field-assessments for field durability and perception of comfort of prototype CB duty uniforms.

- Ft. Lewis, WA with the Maneuver Support Battle Labs (MSBL)
- Pohakuloa and Kaneohe Bases, Hawaii with the Marine Corps and Army MSBL


Transition to JPACE, JIG, SOF, and JCBE

## Impacts:


- Reduced thermal stress
- Reduced logistics burden
- Increased CB agent protection
- Eliminated dependency on charcoal adsorbent



SPM1: Polyallylamine-Based SPM2: Cellulose-Based  
AUIB: Aircrew Uniform Integrated Battlefield (Carbon loaded foam + Gore-Tex fabric)



## AEROSOL PROTECTION



JSLIST: Joint Service Lightweight Integrated Suit Technology

SPM1: Polyallylamine-Based


BDU: Battle Dress Duty Uniform

DPG: Dugway Proving Ground, Utah

MIST: Man-In-Simulant System Vapor Test

## VAPOR PROTECTION


### EVAPORATIVE COOLING POTENTIALS of SPMs vs. VARIOUS CB FABRIC SYSTEMS



Chemical Protective Fabrics I-IV: Various CB Fabric Systems

## REDUCED HEAT STRESS

### High Pressure Hydrostatic Resistance




\*Being Waterproof

## LIQUID PROTECTION

•Many Tests and Evaluation have been conducted to evaluate SPM fabrics; however, **NOISE AND SIZING REMAIN SIGNIFICANT BARRIERS TO OVERCOME.**


# Problems: Noise and Sizing



-Many variations of chemical protective clothing




-Many concerns (Costs, Weight, Logistic, Comfort, Mobility, etc.)



-Multiple sizes


## Material Concept:



## Capability/Enhancement:

- Reduce/Eliminate multiple size requirement
- Conformable Clothing
- Reduce logistic concerns, and improved operational readiness
- Reduced Noise when “being quiet” is important

# Technical Approach --- Prepare dendrimer containing membranes



**Blocking efficiency for dendrimers as a function of the density of the peripheral groups.**




**Dendrimer Packing and Cross Linking shows reactive binding polymer molecules for further filtration efficiency**

# Experimental Results: Dendrimer containing membranes

Methods	MVTR (E96-BW) (g/m <sup>2</sup> /day)	TCE Permeation (E96-BW) (g/m <sup>2</sup> /day)	Special Notes
<b>Hytre/Noveon Membrane (Control – 2mil thick)</b>	<b>1,000 – 2,000</b>	<b>10,000 to 20,000</b>	<b>Elastomeric</b>
<b>1. Estane Coated with dendrimer</b>	<b>2,000</b>	<b>10,000</b>	<b>Elastomeric</b>
<b>2. Estane Cross linked dendrimers</b>	<b>19,000</b>	<b>2,000 – 3,000</b>	<b>Elastomeric</b>
<b>3. Incorporate dendrimers in ICET water based proprietary polymer</b>	<b>3,000</b> <b>WSPC: 2,000-2,800</b>	<b>0</b> <b>WSPC: 0 after 3 hrs</b>	<b>Elastomeric</b>
<b>4. Self-assembled dendrimer</b>	<b>3,000</b> <b>WSPC: 2,000-2,500</b>	<b>0</b> <b>WSPC: 0 after 3 hrs</b>	<b>Not elastomeric</b>
<b>5. PU dispersions mixed with ICET proprietary polymer</b>	<b>To be done</b>	<b>To be done</b>	<b>Elastomeric</b>



# Natick's Water/Simulant Permeation Cell (WSPC) Test Results




**Method 3. Incorporate dendrimers in ICET water based proprietary polymer**



# Water/Simulant Permeation Cell (WSPC) Test Results


## Water Vapor Flux




Method 4. Self-assembled dendrimer

# Static Permeation Test Results

## Static Moisture Vapor Permeation Data (E96-BW)



## Static TCE Vapor Permeation Data (E96-BW)



# **Discussions:**

**Dendrimers are highly hydrophilic and viscous materials. They are very expensive**

**The direct coating on elastomers through anchoring by surface interactions resulted in coatings that never cured.**

**Direct incorporation of dendrimers into polymeric dispersions results in tough but flexible membranes.**

**Using optimal cross-linking of a thin coating appears to overcome this difficulty while dramatically improving the moisture vapor permeation and dramatically reducing cost of the eventual commercial products.**

***This could be a preferred way for optimization for achieving better perm-selectivity.***

## **Conclusions:**

- **Extremely thin coating of cross-linked dendrimer were achieved on water vapor Permeable polyurethane elastomers.**
- **Such coatings improve water vapor transport properties significantly while maintaining resistance to organic vapors.**
- **Further optimization work are underway with ICET, Inc. to develop elastomeric SPMs for resistance to both polar and non-polar molecules.**

## **Recommendations:**

- **Follow on work will be on developing dendritic polymers cross-linked coatings where the cross linking agent is flexible PEO segments with reactive end groups on water vapor permeable polymer materials such as TPU latexes modified with ICET fillers and formulations**

# Acknowledgments:

**Dr. Shantha Sarangapani, Innovative Chemical and Environmental Technologies, Inc. (ICET), Norwood, MA for her dedication in working to Support the US Army Natick Soldier Center's needs to protect our soldiers in Various R&D work since 1985.**